

SIDEKICK® PLUS ADSL FED

TECHNICAL SPECIFICATIONS

MECHANICAL SPECIFICATIONS

Size:	4.6 x 3.1 x 1 in (11.68 x 7.87 x 2.54 cm)
Weight (w/battery):	0.36 lbs (165gm)
Operating Temperature:	-18° C to +60° C (0° F to 140° F)
Storage Temperature:	-40° C to +75° C (-40° F to 167° F)
Battery Life:	Approximately 24 hours of typical use
Battery Shelf Life:	6 months
Replacement Battery:	9 Volt Alkaline



ELECTRICAL SPECIFICATIONS

Strap Resistance:	A/Tip – B/Ring: <math><0.2\Omega</math> A/Tip – T/Gnd: <math><0.2\Omega</math> B/Tip – T/Gnd: <math><0.2\Omega</math>
Input Impedance:	> 100M Ω - A/Tip to B/Ring > 100M Ω - A/Tip to T/Gnd
Voltage Rating:	AC Volts: 150VAC DC Volts: 250VDC
Trace Tones:	Type: Metallic Frequencies: 577Hz and 1004Hz, alternating pulsed Output Impedance: 600 Ω Amplitude: 8 Volts Peak-to-Peak with no load.
Single and Stepped Tones:	400Hz to 100kHz, Sinewave <ul style="list-style-type: none"> 0dBm \pm 0.5dB Output Impedance: <ul style="list-style-type: none"> 600Ω: 400Hz < frequency < 20kHz 135Ω: 20kHz < frequency < 100kHz 100kHz to 1.1MHz, Sinewave <ul style="list-style-type: none"> 0dBm \pm 1.0dB Output Impedance: 135Ω: 100kHz < frequency < 1.1MHz
Tone Output Impedance:	400Hz to 1.1MHz
Longitudinal Balance Termination:	<ul style="list-style-type: none"> IEEE 455-1985 Termination limited to 1 Volt peak Max longitudinal voltage: 8V peak-peak T/G or R/G Metallic Impedance: 736Ω
Longitudinal Impedance:	2,184 Ω
Metallic Terminations:	600 Ω \pm 6.0 Ω 135 Ω \pm 1.3 Ω

USA PHONE 800.642.2155
FAX 760.598.5634

CANADA PHONE 866.384.8813
FAX 800.524.2853

INT'L PHONE +1.815.397.7070
FAX +1.815.397.9247





Operation with the Sidekick® Plus

The Sidekick Plus FED can operate in conjunction with the Sidekick Plus to perform the following measurements:

- K-Test: Far-End-Device straps the pair under test
- TDR: Far-End-Device can alternately short and open the pair to verify the end-of-line
- Noise: Far-End-Device provides a line termination
- Loss: Far-End-Device provides single or multiple reference tones
- Longitudinal Balance: Far-End-Device provides an IEEE 455-1985 Longitudinal Balanced Termination
- Autotest: The Sidekick Plus manages the operation of the Far-End-Device during the test sequence

Connectivity and Test Leads

- Removable, snag resistant RJ45 termination
- Blue Pair: Primary measurement pair and used by the Sidekick Plus to send DTMF command strings to the FED
- Red Pair: Secondary measurement pair
- Yellow Pair: Used for CO/Premise isolation and reconnection
- Green Lead: Connects to the cable Ground for pair to Ground measurements

Environmental

- WEEE
- RoHS
- IP ingress object/water: 3/0

Rating

- Protection Category “0” (formerly known as CAT-I)

Disclaimers and Confidentially

Specifications are subject to change at any time without notice. The information contained in this Technical Specification is the confidential, proprietary information of Greenlee Textron Inc. and, in addition to any restrictions that may apply pursuant to the terms of any Confidentiality or Non-Disclosure Agreement between Greenlee and the recipient (or the recipient's employer), is not to be copied, disclosed or distributed in whole or in part to any third party or used by the recipient in any manner other than the intended purpose for which it was provided to the recipient, without the prior written approval of Greenlee Textron Inc.

Do not read this Specification if you are not the intended recipient. If you are not the intended recipient, or the person responsible for delivering it to the intended recipient, you are hereby notified that any disclosure, copying, distribution, or use of any of the information contained in or attached to this transmission is **STRICTLY PROHIBITED**. If you have received this specification in error, please immediately notify Greenlee and destroy the original specification without reading or saving in any manner.

