


Fiber End Face Criteria Table - PC Polished Connectors (Single Mode Fiber RL ≥ 26 dB)

Zone	Description	Diameter Single Mode	Diameter Multi Mode	Allowable Scratches (Width) Single Mode	Allowable Defects (Diameter) Single Mode	Allowable Scratches (Width) Multi Mode	Allowable Defects (Diameter) Multi Mode
A	Critical Zone	0µm to 25µm	0µm to 65µm	2 ≤ 3µm None > 3µm	2 ≤ 3µm None > 3µm	No Limit ≤ 3µm None > 5µm	4 ≤ 5µm None > 5µm
B	Cladding Zone	25µm to 120µm	65µm to 120µm	No Limit ≤ 3µm 3 > 3µm	No Limit <2µm 5 from 2µm to 5µm None >5µm	No Limit ≤ 5µm None > 5µm	No Limit < 2µm 5 from 2µm to 5µm None > 5µm
C	Adhesive Zone	120µm to 130µm	120µm to 130µm	No Limit	No Limit	No Limit	No Limit
D	Contact Zone	130µm to 250µm	130µm to 250µm	No Limit	None ≥ 10µm	No Limit	None ≥ 10µm



A. Critical Zone

B. Cladding Zone

C. Adhesive Zone

D. Contact Zone