


Product

# KRB 0560



KRB-0560 is a crimping tool for non insulated connectors 6.3 mm, 0.5 - 6 mm<sup>2</sup>/.250", AWG 22-10, B/F-Crimp. Short and long handle available.

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



Die profile



Crimp profile

#### TECHNICAL DATA

**Length:** 256 mm/10.08"

**Width:** 22 mm/0.87"

**Height:** 80 mm/3.15"

**Weight:** 560 gr/1.23 lb

**Wire size:** 0.5-6 mm<sup>2</sup> / AWG 22-AWG 10

**Crimp dimensions mm/mm<sup>2</sup>:**

0,5 - 1,5 mm<sup>2</sup>/1,5 - 2,5 mm<sup>2</sup>/4 - 6 mm<sup>2</sup>

**Crimp dimensions inch/AWG:**

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 - AWG 10

**Connector:** Uninsulated open barrel connectors

**Description:** For uninsulated open barrel connectors.

**Life span, cycles:** 50,000